

PRODUCT DATA SHEET

MA BI 500 / 840

Belt driven two-stage compressor

- Large intake filter designed to reduce noise and optimise compressor performance
- Two stage pump with cast iron cylinder, equipped with large inter aftercoolers for better cooling of the compressed air,
- Output hose designed to improve air cooling,
- Sturdy plastic belt guard that protects all parts in motion, and thanks to the large slots increases ventilation of the pumping unit
- Sturdy resting feet equipped with anti-vibration.







FEATURES

	POWER SUPPLY	400 V / 50 Hz / 3ph	MAX PRESSURE (bar)	11
	MOTOR POWER (kW)	5,5	MAX PRESSURE (psi)	160
	MOTOR POWER (HP)	7,5	SOUND LEVEL (dB)	77
,	AIR PUMP ROTATION SPEED	1250	TANK VOLUME (I)	500
	AIR DISPLACEMENT (I/min)	840	DIMENSIONS (mm)	2010 x 650 x 1330
	AIR DISPLACEMENT (CFM)	29,66	MEGA AIR CODE	2057262

^{*1-}year warranty according to our General Terms of Sales while following the maintenance schedule and respecting the operation and installation recommendation.

PACKAGING

GROSS DIMENSIONS (mm)	2010 x 650 x 1330
GROSS WIGHT (kg)	235

Contact us:

Please contact us for information.

By mail: sales@mega-air.si By phone: +386 (01) 200 68 00

Address: Cesta Dolomitskega odreda 10 || SI −1000 Ljubljana



Don't forget for MEGA PERFORMANCE



^{**}Weight and dimensions are given as information only and are subject to change without prior notice.